

Bullet Series



Bag/Sock Replacement Filters

Our Bag Replacement Filter (Bullet Series) has changed the way that bag filtration vessels are viewed and used. These filters utilize a proprietary string winding approach to create layers of filtration 1.5" deep. This approach traps and removes a larger volume of particles and contaminants than bags/socks. In some applications customers have captured as much as 15 pounds of particulates. Gone are the days of replacing and disposing of bags/socks multiple times per day or week and sketchy performance in capture.

These filters are a direct replacement to #2 filter bags and fit directly into all major manufacturer baskets.

Features/Benefits:

- Extend time between change-outs and reduce downtime.
- Extremely efficient in capturing and lowering Total Suspended Solids (TSS).
- Save on labor costs, disposal and liability associated with frequent change-outs.
- Reduce ruptures that can contaminate your process.
- Protect wells and pumps with increased water quality.

MEDIA OPTIONS: Polypropylene (EP), FDA Polypropylene (FP)

CENTER CORE: Polypropylene

TOP CAP: 304 S/S

BOTTOM CAP: Polypropylene

LENGTH: 10" (#1 Bag) 24" (#2 Bag)

RECOMMENDED CHANGEOUT: 35 PSID

FLOW RATE: 80-125 GPM (Depending on fluid type)

MAX TEMPERATURE: 160°F

MICRON RATING EFFICIENCY RANGES (Estimated):

Bullet-A - Ranges from .5 Micron (90%) to 15 Micron (98%)

Bullet-B - Ranges from 10 Micron (90%) to 50 Micron (98%)

Bullet-C - Ranges from 50 Micron (90%) to 125 Micron (98%)

Bullet-D - Ranges from 125 Micron (90%) to 200 Micron (98%)

Bullet-E - Ranges from 200 Micron (90%) to 250 Micron (98%)

Bullet-F - Ranges from 250 Micron (90%) to 300 Micron (98%)

* Other ranges available upon request.



**500 Cubic Inches of
Depth Filtration.**

